

Description

Hole Diameter: 7/8",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS14183LC14
Minimum Qty (MOQ):	5
NSN:	5310-01-543-2038
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N MS14183L-C14 Specifications

<b>Hole Diameter:</b>	0.914 Inches Minimum And 0.918 Inches Maximum
<b>Outside Diameter:</b>	1.615 Inches Minimum And 1.625 Inches Maximum
<b>Recess Diameter:</b>	1.182 Inches Minimum And 1.192 Inches Maximum
<b>Material Thickness:</b>	0.137 Inches Minimum And 0.147 Inches Maximum
<b>End Item Identification:</b>	F-22 Raptor
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
<b>Recess Angle:</b>	45.0 Degrees Nominal
<b>Surface Finish:</b>	125.0 Microinches All Surfaces
<b>Part Name Assigned By Controlling Agency:</b>	Washer,countersunk And Plain
<b>Material:</b>	Nickel Alloy 718 Overall
<b>Material Document And Classification:</b>	Ams 5696 Assn Std Single Material Response Overall Or Ams 5597 Assn Std Single Material Response Overall Or Ams 5662 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall Or Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall Or Cda000 Type 2, Class 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	15 Recessed

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS14183L-C14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.