

Description

Hole Diameter: 7/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | MS14183LC14 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5310-01-543-2038 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N MS14183L-C14 Specifications

| | |
|---|--|
| Hole Diameter: | 0.914 Inches Minimum And 0.918 Inches Maximum |
| Outside Diameter: | 1.615 Inches Minimum And 1.625 Inches Maximum |
| Recess Diameter: | 1.182 Inches Minimum And 1.192 Inches Maximum |
| Material Thickness: | 0.137 Inches Minimum And 0.147 Inches Maximum |
| End Item Identification: | F-22 Raptor |
| Hardness Rating: | 36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum |
| Recess Angle: | 45.0 Degrees Nominal |
| Surface Finish: | 125.0 Microinches All Surfaces |
| Part Name Assigned By Controlling Agency: | Washer,countersunk And Plain |
| Material: | Nickel Alloy 718 Overall |
| Material Document And Classification: | Ams 5696 Assn Std Single Material Response Overall Or Ams 5597 Assn Std Single Material Response Overall Or Ams 5662 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall Or Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall Or Cda000 Type 2, Class 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | 15 Recessed |

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS14183L-C14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.