

Description

Hole Diameter: 1/4", Diameter: 3/8", Thickness: 1/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS14183LC3](#)

SKU / Model:	MS14183LC3
Minimum Qty (MOQ):	10
NSN:	5310-01-464-0179
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS14183L-C3 Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.238 Inches Minimum And 0.248 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Overall Diameter:	0.362 Inches Minimum And 0.372 Inches Maximum
Hardness Rating:	36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
Inside Left Corner Chamfer Angle:	45.0 Degrees Nominal
Inside Right Corner Chamfer Angle:	45.0 Degrees Nominal
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams5596 Assn Std Single Material Response Overall Or Ams5597 Assn Std Single Material Response Overall Or Ams5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS14183L-C3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.