

**Description**

MS14183L-C4 Recessed Washer

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14183LC4
Minimum Qty (MOQ):	5
NSN:	5310-01-323-2920
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



NO IMAGE  
AVAILABLE

## P/N MS14183L-C4 Specifications

<b>Hole Diameter:</b>	0.251 Inches Minimum And 0.255 Inches Maximum
<b>Outside Diameter:</b>	0.460 Inches Minimum And 0.470 Inches Maximum
<b>Recess Diameter:</b>	0.310 Inches Minimum And 0.320 Inches Maximum
<b>Material Thickness:</b>	0.057 Inches Minimum And 0.069 Inches Maximum
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
<b>Recess Angle:</b>	90.0 Degrees Nominal
<b>Material:</b>	Nickel Alloy 718 Overall
<b>Material Document And Classification:</b>	Ams 5596 Assn Std Single Material Response Overall Or Ams 5597 Assn Std Single Material Response Overall Or Ams 5662 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	15 Recessed

## How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS14183L-C4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.