

Description

MS14183L-C4 Recessed Washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS14183LC4
Minimum Qty (MOQ):	5
NSN:	5310-01-323-2920
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



P/N MS14183L-C4 Specifications

Hole Diameter:	0.251 Inches Minimum And 0.255 Inches Maximum
Outside Diameter:	0.460 Inches Minimum And 0.470 Inches Maximum
Recess Diameter:	0.310 Inches Minimum And 0.320 Inches Maximum
Material Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Hardness Rating:	36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
Recess Angle:	90.0 Degrees Nominal
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5596 Assn Std Single Material Response Overall Or Ams 5597 Assn Std Single Material Response Overall Or Ams 5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS14183L-C4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.