

**Description**

Hole Diameter: 1/2", MS14183 series washer

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS14183LC8](#)

SKU / Model:	MS14183LC8
Minimum Qty (MOQ):	10
NSN:	5310-01-306-7880
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

## P/N MS14183L-C8 Specifications

<b>Hole Diameter:</b>	0.501 Inches Minimum And 0.505 Inches Maximum
<b>Outside Diameter:</b>	0.922 Inches Minimum And 0.932 Inches Maximum
<b>Recess Diameter:</b>	0.614 Inches Minimum And 0.624 Inches Maximum
<b>Material Thickness:</b>	0.071 Inches Minimum And 0.085 Inches Maximum
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
<b>Recess Angle:</b>	90.0 Degrees Nominal
<b>Material:</b>	Nickel Alloy 718 Overall
<b>Material Document And Classification:</b>	Ams 5596 Assn Std Single Material Response Overall Or Ams 5597 Assn Std Single Material Response Overall Or Ams 5662 Assn Std Single Material Response Overall
<b>Style Designator:</b>	15 Recessed

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS14183L-C8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.