

Description

Hole Diameter: 3/8", nickel alloy material, MS14183 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS14183-LC12](#) [MS14183L-C12](#)

SKU / Model:	MS14183LC12
Minimum Qty (MOQ):	5
NSN:	5310-01-490-3137
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS14183LC12 Specifications

Hole Diameter:	0.078 Inches Minimum And 0.793 Inches Maximum
Outside Diameter:	1.384 Inches Minimum And 1.394 Inches Maximum
Recess Diameter:	0.981 Inches Minimum And 0.991 Inches Maximum
Material Thickness:	0.099 Inches Minimum And 0.119 Inches Maximum
Hardness Rating:	36.0 Rockwell C Minimum Or 45.0 Rockwell C Maximum
Recess Angle:	44.0 Degrees Minimum And 46.0 Degrees Maximum
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams5596 Assn Std Single Material Response Overall Or Ams5597 Assn Std Single Material Response Overall Or Ams5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Shouldered And Recessed

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS14183LC12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.