

P/N MS14210-L06-14

Description

Thread Size: 1/8", Nut Length: 3/8", Nut Height: 7/16", Head Width: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS14210L0614

Minimum Qty (MOQ): 1 EA

NSN: 5310-01-354-8501

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS14210-L06-14 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Pilot Diameter:	0.217 Inches Maximum
Pilot Length:	0.254 Inches Nominal
Counterbore Diameter:	0.182 Inches Nominal Nut
Lubrication:	Dry Film Lubricant
Nut Style:	Spline (floating)
Nut Length:	0.435 Inches Maximum
Nut Height:	0.468 Inches Nominal
Nut Counterbore Depth:	0.316 Inches Nominal Nut
Width Across Flats:	0.310 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Material:	Iron Alloy 660 Nut
Material:	Steel Comp 304 Base Or Steel Comp 305 Base
Material:	Steel Comp 631 Bracket
Material Document And Classification:	Ams 5528 Assn Std Single Material Response Bracket
Material Document And Classification:	Ams 5639 Assn Std 1st Material Response Base Or Ams 5514 Assn Std 2nd Material Response Base
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Nut
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS14210-L06-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.