



★ FASTENERS

Military-Fasteners.com

P/N MS14218AD4-10

Description


Fastener Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS14218AD410
Minimum Qty (MOQ):	100
NSN:	5320-01-481-9331
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS14218AD4-10 Specifications

Fastener Length:	0.625 Inches Nominal
Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.027 Inches Nominal
Shank Diameter:	0.124 Inches Minimum And 0.127 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.160 Inches Minimum And 0.162 Inches Maximum
End Item Identification:	F/a-18 E/f Aircraft
Countersink Angle:	30.0 Degrees Nominal
Criticality Code Justification:	Agav
Special Features:	Rivet Has Dot On Head With A Maximum Depth Of 0.030 Inches And And Maximum Width Of 0.050 Inches
Material:	Aluminum Alloy 2117 Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Type 2, Class 1 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD4-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.