

P/N MS14218AD4-10

Description

Fastener Length: 5/8

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS14218AD410

Minimum Qty (MOQ): 100

NSN: 5320-01-481-9331

Schedule B: 7616.10.3000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









P/N MS14218AD4-10 Specifications

| Fastener Length: | 0.625 Inches Nominal |
|--|--|
| Head Style: | Countersunk W/ Reverse Chamfer |
| Head Height: | 0.027 Inches Nominal |
| Shank Diameter: | 0.124 Inches Minimum And 0.127 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.160 Inches Minimum And 0.162 Inches Maximum |
| End Item Identification: | F/a-18 E/f Aircraft |
| Countersink Angle: | 30.0 Degrees Nominal |
| Criticality Code Justification: | Agav |
| Special Features: | Rivet Has Dot On Head With A Maximum Depth Of 0.030 Inches And And Maximum Width Of 0.050 Inches |
| Material: | Aluminum Alloy 2117 Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625, Type 2, Class 1 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS14218AD4-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/MS14218AD4-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/MS14218AD4-10 and selecting the quantity you want then