

**Description**

Fastener Length: 0-63/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14218AD416
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-268-5820
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS14218AD4-16 Specifications

<b>Fastener Length:</b>	0.990 Inches Minimum And 1.010 Inches Maximum
<b>Head Style:</b>	Countersunk W/ Reverse Chamfer
<b>Head Height:</b>	0.033 Inches Nominal
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.127 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.162 Inches Maximum
<b>Minimum Tensile Strength:</b>	38000 Pounds Per Square Inch
<b>Minimum Yield Strength:</b>	180000 Pounds Per Square Inch
<b>Shear Strength:</b>	26000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	118.5 Degrees Minimum And 121.5 Degrees Maximum
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall Or Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,ty 2 Cl 1 Mil Spec 1st Treatment Response Overall Or Mil-c-5541,cl 1a Mil Spec 2nd Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD4-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.