

Description

Fastener Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MS14218AD416 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-01-268-5820 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MS14218AD4-16 Specifications

| | |
|---|--|
| Fastener Length: | 0.990 Inches Minimum And 1.010 Inches Maximum |
| Head Style: | Countersunk W/ Reverse Chamfer |
| Head Height: | 0.033 Inches Nominal |
| Shank Diameter: | 0.124 Inches Minimum And 0.127 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.162 Inches Maximum |
| Minimum Tensile Strength: | 38000 Pounds Per Square Inch |
| Minimum Yield Strength: | 180000 Pounds Per Square Inch |
| Shear Strength: | 26000 Single Pounds Per Square Inch |
| Countersink Angle: | 118.5 Degrees Minimum And 121.5 Degrees Maximum |
| Heat Treatment: | T-4 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Chromate Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,ty 2 Cl 1 Mil Spec 1st Treatment Response Overall Or Mil-c-5541,cl 1a Mil Spec 2nd Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD4-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.