

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | MS14218AD43         |
| Minimum Qty (MOQ):      | 65 EA               |
| NSN:                    | 5320-01-285-7748    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE  
AVAILABLE

## P/N MS14218AD4-3 Specifications

|   |   |
|---|---|
| <b>Fastener Length:</b>                               | 0.178 Inches Minimum And 0.198 Inches Maximum                   |
| <b>Head Style:</b>                                    | Countersunk W/ Reverse Chamfer                                  |
| <b>Head Height:</b>                                   | 0.027 Inches Nominal  |
| <b>Shank Diameter:</b>                                | 0.124 Inches Minimum And 0.127 Inches Maximum                   |
| <b>Shank Style:</b>                                   | Straight W/radius Chamfered Tip                                 |
| <b>Head Major Diameter:</b>                           | 0.162 Inches Maximum  |
| <b>Minimum Tensile Strength:</b>                      | 38000 Pounds Per Square Inch                                    |
| <b>Minimum Yield Strength:</b>                        | 18000 Pounds Per Square Inch                                    |
| <b>Shear Strength:</b>                                | 26000 Single Pounds Per Square Inch                             |
| <b>Countersink Angle:</b>                             | 118.5 Degrees Minimum And 121.5 Degrees Maximum                 |
| <b>Heat Treatment:</b>                                | T-4 Solution Heat Treated Overall                               |
| <b>Material:</b>                                      | Aluminum Alloy 2117 Overall                                     |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Overall              |
| <b>Surface Treatment:</b>                             | Anodize Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625,ty 2,cl 1 Mil Spec Single Treatment Response Overall |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD4-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.