

**Description**

Fastener Length: 7/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14218AD43R
Minimum Qty (MOQ):	60 EA
NSN:	5320-01-549-7216
Schedule B:	7616.10.3000
ECCN:	EAR99



NO IMAGE  
AVAILABLE

## P/N MS14218AD4-3R Specifications

<b>Fastener Length:</b>	0.219 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.125 Inches Nominal
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.162 Inches Minimum And 0.164 Inches Maximum
<b>Countersink Angle:</b>	120.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625, Type II, Class 1 Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas-14218 Professional/Industrial Association Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD4-3R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.