

Description

Fastener Length: 7/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14218AD43R
Minimum Qty (MOQ):	60 EA
NSN:	5320-01-549-7216
Schedule B:	7616.10.3000
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N MS14218AD4-3R Specifications

Fastener Length:	0.219 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.162 Inches Minimum And 0.164 Inches Maximum
Countersink Angle:	120.0 Degrees Nominal
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Type II, Class 1 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas-14218 Professional/Industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD4-3R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.