

Description

Fastener Length: 1/2, roughly 1850 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS14218AD48 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-529-1487 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N MS14218AD4-8 Specifications

| | |
|---|--|
| Fastener Length: | 0.500 Inches Nominal |
| Head Style: | Countersunk W/ Reverse Chamfer |
| Head Height: | 0.027 Inches Nominal |
| Shank Diameter: | 0.124 Inches Minimum And 0.127 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.160 Inches Minimum And 0.162 Inches Maximum |
| End Item Identification: | F/a-18 E Aircraft |
| Countersink Angle: | 30.0 Degrees Nominal |
| Criticality Code Justification: | Agav |
| Special Features: | Rivet Has Dot On Head With Maximum Depth Of 0.030 Inches And A Maximum Width Of 0.050 Inches |
| Material: | Aluminum Alloy 2117 Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625, Type 2, Class 1 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD4-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.