

Description

Fastener Length: 3/4, roughly 740 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS14218AD511
Minimum Qty (MOQ):	100
NSN:	5320-01-497-4415
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N MS14218AD5-11 Specifications

Fastener Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.035 Inches Nominal
Shank Diameter:	0.155 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.208 Inches Minimum And 0.210 Inches Maximum
End Item Identification:	Aircraft, Hornet, F/a-18
Countersink Angle:	118.5 Degrees Minimum And 121.5 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Specification/standard Data:	80205-nas-14218 Professional/Industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD5-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.