

**Description**

Fastener Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14218AD55R
Minimum Qty (MOQ):	100
NSN:	5320-01-362-2909
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N MS14218AD5-5R Specifications

<b>Fastener Length:</b>	0.333 Inches Minimum And 0.353 Inches Maximum
<b>Head Style:</b>	Countersunk W/ Reverse Chamfer
<b>Head Height:</b>	0.035 Inches Nominal
<b>Shank Diameter:</b>	0.1562 Inches Nominal
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.210 Inches Nominal
<b>Minimum Tensile Strength:</b>	38000 Pounds Per Square Inch
<b>Minimum Yield Strength:</b>	18000 Pounds Per Square Inch
<b>Countersink Angle:</b>	120.0 Degrees Nominal
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD5-5R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.