

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS14218AD56R |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-467-7883 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N MS14218AD5-6R Specifications

| | |
|--|---|
| Fastener Length: | 0.406 Inches Nominal |
| Head Style: | Countersunk W/ Reverse Chamfer |
| Head Height: | 0.035 Inches Nominal |
| Shank Diameter: | 0.156 Inches Nominal |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.210 Inches Nominal |
| End Item Identification: | Airlifter;c-17 Air Craft |
| Countersink Angle: | 120.0 Radians Nominal |
| Part Name Assigned By Controlling Agency: | Solid Rivet For Forward Ramp Fairing Installation |
| Material: | Aluminum Alloy 2117 Overall Or Titanium Alloy Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD5-6R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.