



★ FASTENERS

Military-Fasteners.com

P/N MS14218AD5-7

Description

Fastener Length: 1/2", roughly 1160 pieces per pound, MS14218 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS14218AD57
Minimum Qty (MOQ):	100
NSN:	5320-01-267-4770
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS14218AD5-7 Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.221 Inches Minimum And 0.224 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.208 Inches Minimum And 0.210 Inches Maximum
Grip Length:	0.100 Nominal Inches
Minimum Tensile Strength:	38000 Pounds Per Square Inch
Minimum Yield Strength:	18000 Pounds Per Square Inch
Shear Strength:	26000 Single Pounds Per Square Inch
Countersink Angle:	105.0 Degrees Minimum And 135.0 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Mil Std Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 11,class 1 Mil Std Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD5-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.