

**Description**

Fastener Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS14218AD58R
Minimum Qty (MOQ):	100
NSN:	5320-01-485-5720
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS14218AD5-8R Specifications

<b>Fastener Length:</b>	0.531 Inches Nominal
<b>Head Style:</b>	Countersunk W/ Reverse Chamfer
<b>Head Height:</b>	0.035 Inches Nominal
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.158 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.208 Inches Minimum And 0.210 Inches Maximum
<b>End Item Identification:</b>	Pylon, Aircraft
<b>Countersink Angle:</b>	30.0 Degrees Nominal
<b>Criticality Code Justification:</b>	Agav
<b>Special Features:</b>	Rivet Has Dot On Head With Maximum Depth Of 0.030 Inches And Maximum Width Of 0.050 Inches
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625, Type 2, Class 1 Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD5-8R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.