

Description

Fastener Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14218AD58R
Minimum Qty (MOQ):	100
NSN:	5320-01-485-5720
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in all caps.

NO IMAGE
AVAILABLE

P/N MS14218AD5-8R Specifications

Fastener Length:	0.531 Inches Nominal
Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.035 Inches Nominal
Shank Diameter:	0.155 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.208 Inches Minimum And 0.210 Inches Maximum
End Item Identification:	Pylon, Aircraft
Countersink Angle:	30.0 Degrees Nominal
Criticality Code Justification:	Agav
Special Features:	Rivet Has Dot On Head With Maximum Depth Of 0.030 Inches And Maximum Width Of 0.050 Inches
Material:	Aluminum Alloy 2117 Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Type 2, Class 1 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD5-8R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.