

Description

Fastener Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS14218AD58R |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-485-5720 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



NO IMAGE
AVAILABLE

P/N MS14218AD5-8R Specifications

| | |
|---|--|
| Fastener Length: | 0.531 Inches Nominal |
| Head Style: | Countersunk W/ Reverse Chamfer |
| Head Height: | 0.035 Inches Nominal |
| Shank Diameter: | 0.155 Inches Minimum And 0.158 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.208 Inches Minimum And 0.210 Inches Maximum |
| End Item Identification: | Pylon, Aircraft |
| Countersink Angle: | 30.0 Degrees Nominal |
| Criticality Code Justification: | Agav |
| Special Features: | Rivet Has Dot On Head With Maximum Depth Of 0.030 Inches And Maximum Width Of 0.050 Inches |
| Material: | Aluminum Alloy 2117 Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625, Type 2, Class 1 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD5-8R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.