

Description

Fastener Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14218AD59
Minimum Qty (MOQ):	100
NSN:	5320-01-250-9677
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



NO IMAGE
AVAILABLE

P/N MS14218AD5-9 Specifications

Identification Code Color:	Orange
Fastener Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.034 Inches Minimum And 0.039 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.210 Inches Maximum
Shear Strength:	26000 Single Pounds Per Square Inch
Countersink Angle:	119.5 Degrees Minimum And 120.5 Degrees Maximum
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2,cl 2 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD5-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.