

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | MS14218AD5C9 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-01-470-8275 |



P/N MS14218AD5C9 Specifications

| | |
|-----------------------------|---|
| Fastener Length: | 0.552 Inches Minimum And 0.572 Inches Maximum |
| Head Style: | Countersunk W/ Reverse Chamfer |
| Head Height: | 0.069 Inches Nominal |
| Shank Diameter: | 0.282 Inches Minimum And 0.285 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.403 Inches Minimum And 0.405 Inches Maximum |
| Countersink Angle: | 118.0 Degrees Minimum And 122.0 Degrees Maximum |
| Material: | Aluminum Alloy 2117 Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD5C9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.