

Description

Fastener Length: 3/8, roughly 760 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS14218AD66                               |
| Minimum Qty (MOQ):      | 1 Pound                                   |
| NSN:                    | 5320-01-391-1622                          |
| Schedule B:             | 7616.10.3000                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



\* See page 2 for technical characteristics

## P/N MS14218AD6-6 Specifications

|   |   |
|---|---|
| <b>Fastener Length:</b>                               | 0.365 Inches Minimum And 0.385 Inches Maximum                     |
| <b>Head Style:</b>                                    | Countersunk W/ Reverse Chamfer                                    |
| <b>Head Height:</b>                                   | 0.044 Inches Nominal  |
| <b>Shank Diameter:</b>                                | 0.186 Inches Minimum And 0.189 Inches Maximum                     |
| <b>Shank Style:</b>                                   | Straight W/radius Chamfered Tip                                   |
| <b>Head Major Diameter:</b>                           | 0.256 Inches Minimum And 0.258 Inches Maximum                     |
| <b>Minimum Tensile Strength:</b>                      | 38000 Pounds Per Square Inch                                      |
| <b>Minimum Yield Strength:</b>                        | 18000 Pounds Per Square Inch                                      |
| <b>Shear Strength:</b>                                | 26000 Single Pounds Per Square Inch                               |
| <b>Countersink Angle:</b>                             | 118.5 Degrees Minimum And 121.5 Degrees Maximum                   |
| <b>Heat Treatment:</b>                                | T-4 Solution Heat Treated Overall                                 |
| <b>Material:</b>                                      | Aluminum Alloy 2117 Overall                                       |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Overall                |
| <b>Surface Treatment:</b>                             | Anodize Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625, Ty 2, Cl 1 Mil Spec Single Treatment Response Overall |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218AD6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.