

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS14218E410 |
| Minimum Qty (MOQ): | 145 EA |
| NSN: | 5320-01-391-2185 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS14218E4-10 Specifications

| | |
|---|---|
| Fastener Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Head Style: | Countersunk W/ Reverse Chamfer |
| Head Height: | 0.027 Inches Nominal |
| Shank Diameter: | 0.124 Inches Minimum And 0.127 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.160 Inches Minimum And 0.162 Inches Maximum |
| Minimum Tensile Strength: | 68000 Pounds Per Square Inch |
| Minimum Yield Strength: | 58000 Pounds Per Square Inch |
| Shear Strength: | 41000 Single Pounds Per Square Inch |
| Countersink Angle: | 118.5 Degrees Minimum And 121.5 Degrees Maximum |
| Heat Treatment: | T-73 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 7075 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625, Ty 2, Cl 2 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E4-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.