

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14218E411
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-536-7050
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS14218E4-11 Specifications

Fastener Length:	0.687 Inches Nominal
Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.027 Inches Nominal
Shank Diameter:	0.124 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.162 Inches Nominal
End Item Identification:	Fighter Aircraft-first (f18 E/f)
Minimum Tensile Strength:	68000 Pounds Per Square Inch
Minimum Yield Strength:	58000 Pounds Per Square Inch
Countersink Angle:	120.0 Degrees Nominal
Criticality Code Justification:	Agav
Special Features:	Material Identification Symbol For 7075 Of A Ring. .100 Max Tall And Indented .030 Max Depth.
Material:	Aluminum Alloy 7075 Overall
Surface Treatment:	Anodize Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E4-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.