

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14218E45R
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-542-3387
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS14218E4-5R Specifications

Identification Code Color:	Natural
Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.033 Inches Nominal
Shank Diameter:	0.124 Inches Minimum And 0.127 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.162 Inches Maximum
Countersink Angle:	118.5 Degrees Minimum And 121.5 Degrees Maximum
Special Features:	Rivet Increased Length By .031 - Inch
Heat Treatment:	T-73 Solution Heat Treated Overall
Material:	Aluminum Alloy Overall
Material Document And Classification:	23-120 7050 Fscm 7630 Mfr Ref Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Ty 2 Cl 2 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E4-5R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.