

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS14218E46
Minimum Qty (MOQ):	145 EA
NSN:	5320-01-264-9419
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS14218E4-6 Specifications

Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.004 Inches Minimum And 0.008 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.127 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.160 Inches Minimum And 0.162 Inches Maximum
Grip Length:	0.188 Nominal Inches
Countersink Angle:	118.5 Degrees Minimum And 121.5 Degrees Maximum
Special Features:	Optional Plain End May Be Furnished
Heat Treatment:	T-73 Solution Heat Treated Overall
Material:	Aluminum Alloy 7050 Overall
Material Document And Classification:	23-120,cagec 76301 Mfr Ref Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2,cl 2 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E4-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.