

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14218E56
Minimum Qty (MOQ):	100
NSN:	5320-01-218-9852
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS14218E5-6 Specifications

Identification Code Color:	Natural
Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.042 Inches Nominal
Shank Diameter:	0.155 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.210 Inches Maximum
Countersink Angle:	118.5 Degrees Minimum And 121.5 Degrees Maximum
Material:	Aluminum Alloy Overall
Material Document And Classification:	23-120,comp 7050,t73,fscm 76301 Mfr Ref Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty2,cl2 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E5-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.