

P/N MS14218E5-6R

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS14218E56R

Minimum Qty (MOQ): 10 EA

NSN: 5320-01-311-6330

Schedule B: 7616.10.3000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N MS14218E5-6R Specifications

Fastener Length:	0.406 Inches Nominal
Head Style:	Countersunk W/ Reverse Chamfer
Shank Diameter:	0.156 Inches Nominal
Part Name Assigned By Controlling Agency:	Rivet, Solid, 120 Deg Flush Interference Shear Head
Material:	Aluminum Alloy Overall
Surface Treatment Document And Classification:	Mil-a-8625, Ty Ii, Class 1, Dichromate Seal Fed Spec Single Treatment Response Overall
Specification/standard Data:	96906-ms14218 Government Standard

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS14218E5-6R and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/MS14218E5-6R and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/MS14218E5-6R and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/MS14218E5-6R and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/ms14218E5-6R and selecting the quantity you want then cart in the property of the proper