

**Description**

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS14218E56R                                 |
| Minimum Qty (MOQ):      | 10 EA                                       |
| NSN:                    | 5320-01-311-6330                            |
| Schedule B:             | 7616.10.3000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

## P/N MS14218E5-6R Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.406 Inches Nominal   |
| <b>Head Style:</b>                                    | Countersunk W/ Reverse Chamfer   |
| <b>Shank Diameter:</b>                                | 0.156 Inches Nominal   |
| <b>Part Name Assigned By Controlling Agency:</b>      | Rivet, Solid, 120 Deg Flush Interference Shear Head                                    |
| <b>Material:</b>                                      | Aluminum Alloy Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625, Ty li, Class 1, Dichromate Seal Fed Spec Single Treatment Response Overall |
| <b>Specification/standard Data:</b>                   | 96906-ms14218 Government Standard  |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E5-6R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.