

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS14218E611
Minimum Qty (MOQ):	85 EA
NSN:	5320-01-311-8745
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N MS14218E6-11 Specifications

Identification Code Color:	Gold
Fastener Length:	0.344 Inches Nominal
Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.044 Inches Nominal
Shank Diameter:	0.187 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.258 Inches Nominal
Minimum Tensile Strength:	68000 Pounds Per Square Inch
Countersink Angle:	120.0 Degrees Nominal
Material:	Aluminum Alloy 7075 Overall
Surface Treatment:	Anodize Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E6-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.