

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS14218E64
Minimum Qty (MOQ):	65 EA
NSN:	5320-01-359-6976
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS14218E6-4 Specifications

Fastener Length:	0.2400 Inches Minimum And 0.2600 Inches Maximum
Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.0440 Inches Nominal
Shank Diameter:	0.1860 Inches Minimum And 0.1890 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.2560 Inches Minimum And 0.2580 Inches Maximum
Countersink Angle:	118.5 Degrees Minimum And 121.5 Degrees Maximum
Material:	Aluminum Alloy 7050 Overall
Surface Treatment:	Anodize Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E6-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.