

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MS14218E64 |
| Minimum Qty (MOQ): | 65 EA |
| NSN: | 5320-01-359-6976 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MS14218E6-4 Specifications

| | |
|-----------------------------|---|
| Fastener Length: | 0.2400 Inches Minimum And 0.2600 Inches Maximum |
| Head Style: | Countersunk W/ Reverse Chamfer |
| Head Height: | 0.0440 Inches Nominal |
| Shank Diameter: | 0.1860 Inches Minimum And 0.1890 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.2560 Inches Minimum And 0.2580 Inches Maximum |
| Countersink Angle: | 118.5 Degrees Minimum And 121.5 Degrees Maximum |
| Material: | Aluminum Alloy 7050 Overall |
| Surface Treatment: | Anodize Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E6-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.