

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS14218E66R |
| Minimum Qty (MOQ): | 250 EA |
| NSN: | 5320-01-391-2342 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS14218E6-6R Specifications

| | |
|---|---|
| Fastener Length: | 0.396 Inches Minimum And 0.416 Inches Maximum |
| Head Style: | Countersunk W/ Reverse Chamfer |
| Head Height: | 0.044 Inches Nominal |
| Shank Diameter: | 0.186 Inches Minimum And 0.189 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.256 Inches Minimum And 0.258 Inches Maximum |
| Minimum Tensile Strength: | 68000 Pounds Per Square Inch |
| Minimum Yield Strength: | 58000 Pounds Per Square Inch |
| Countersink Angle: | 118.5 Degrees Minimum And 121.5 Degrees Maximum |
| Heat Treatment: | T-4 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 7050 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625, Ty 2, Cl 1 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E6-6R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.