

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS14218E67R
Minimum Qty (MOQ):	255 EA
NSN:	5320-01-391-5491
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS14218E6-7R Specifications

Fastener Length:	0.470 Inches Nominal
Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.044 Inches Nominal
Shank Diameter:	0.186 Inches Minimum And 0.189 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.256 Inches Minimum And 0.258 Inches Maximum
Minimum Tensile Strength:	68000 Pounds Per Square Inch
Minimum Yield Strength:	58000 Pounds Per Square Inch
Countersink Angle:	118.5 Degrees Minimum And 121.5 Degrees Maximum
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 7050 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Ty 2, Cl 1 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E6-7R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.