

**Description**

MS14218E6-9

\* Manufacturer certifications are shipped with your order FREE of charge

[Order this part online](#)**Additional Information**

SKU / Model:	MS14218E69
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-313-7617
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS14218E6-9 Specifications

<b>Identification Code Color:</b>	Gold
<b>Fastener Length:</b>	0.0281 Inches Nominal
<b>Head Style:</b>	Countersunk W/ Reverse Chamfer
<b>Head Height:</b>	0.044 Inches Nominal
<b>Shank Diameter:</b>	0.187 Inches Nominal
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.258 Inches Nominal
<b>Minimum Tensile Strength:</b>	68000 Pounds Per Square Inch
<b>Countersink Angle:</b>	120.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 7075 Overall
<b>Surface Treatment:</b>	Anodize Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E6-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.