

**Description**

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14218E810
Minimum Qty (MOQ):	45 EA
NSN:	5320-01-155-4410
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N MS14218E8-10 Specifications

<b>Fastener Length:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Head Style:</b>	Countersunk W/ Reverse Chamfer
<b>Head Height:</b>	0.0695 Inches Nominal
<b>Shank Diameter:</b>	0.249 Inches Minimum And 0.252 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.358 Inches Maximum
<b>Countersink Angle:</b>	119.5 Degrees Minimum And 120.5 Degrees Maximum
<b>Special Features:</b>	Aluminum Alloy 7050;color Gold
<b>Material:</b>	Aluminum Alloy Overall
<b>Material Document And Classification:</b>	T-73 23-120,fscm 76301 Mfr Ref Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E8-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.