

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS14218E810
Minimum Qty (MOQ):	45 EA
NSN:	5320-01-155-4410
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS14218E8-10 Specifications

Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.0695 Inches Nominal
Shank Diameter:	0.249 Inches Minimum And 0.252 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.358 Inches Maximum
Countersink Angle:	119.5 Degrees Minimum And 120.5 Degrees Maximum
Special Features:	Aluminum Alloy 7050;color Gold
Material:	Aluminum Alloy Overall
Material Document And Classification:	T-73 23-120,fscm 76301 Mfr Ref Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E8-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.