

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MS14218E813 |
| Minimum Qty (MOQ): | 65 EA |
| NSN: | 5320-01-163-0624 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MS14218E8-13 Specifications

| | |
|---|---|
| Identification Code Color: | Natural |
| Fastener Length: | 0.802 Inches Minimum And 0.822 Inches Maximum |
| Head Style: | Countersunk W/ Reverse Chamfer |
| Head Height: | 0.061 Inches Nominal |
| Shank Diameter: | 0.249 Inches Minimum And 0.252 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.358 Inches Maximum |
| Countersink Angle: | 118.5 Degrees Minimum And 121.5 Degrees Maximum |
| Heat Treatment: | T-73 Solution Heat Treated Overall |
| Material: | Aluminum Alloy Overall |
| Material Document And Classification: | 23-120,alloy 7050,fscm 76301 Mfr Ref Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Ty 2 Cl 2 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E8-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.