

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14218E813
Minimum Qty (MOQ):	65 EA
NSN:	5320-01-163-0624
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N MS14218E8-13 Specifications

Identification Code Color:	Natural
Fastener Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.061 Inches Nominal
Shank Diameter:	0.249 Inches Minimum And 0.252 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.358 Inches Maximum
Countersink Angle:	118.5 Degrees Minimum And 121.5 Degrees Maximum
Heat Treatment:	T-73 Solution Heat Treated Overall
Material:	Aluminum Alloy Overall
Material Document And Classification:	23-120,alloy 7050,fscm 76301 Mfr Ref Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Ty 2 Cl 2 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218E8-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.