

P/N MS14218T5-12

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS14218T512

Minimum Qty (MOQ): 10 EA

NSN: 5320-01-191-2912

Schedule B: 8108.90.3060

ECCN: EAR99

National Motor Freight: 136500, Metal Noi / Metal Alloys Noi



^{*} See page 2 for technical characteristics

P/N MS14218T5-12 Specifications

| Fastener Length: | 0.740 Inches Minimum And 0.760 Inches Maximum |
|---------------------------------------|--|
| Head Style: | Countersunk W/ Reverse Chamfer |
| Head Height: | 0.042 Inches Nominal |
| Shank Diameter: | 0.155 Inches Minimum And 0.158 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.210 Inches Maximum |
| Countersink Angle: | 118.5 Degrees Minimum And 121.5 Degrees Maximum |
| Material: | Titanium Alloy Uns R58450 Overall |
| Material Document And Classification: | Ams 4982 Assn Std Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS14218T5-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.