

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS14218T55R
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-367-6393
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N MS14218T5-5R Specifications

Fastener Length:	0.3330 Inches Minimum And 0.3530 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.1550 Inches Minimum And 0.1580 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.2080 Inches Minimum And 0.2100 Inches Maximum
Minimum Tensile Strength:	65000 Pounds Per Square Inch
Minimum Yield Strength:	60000 Pounds Per Square Inch
Countersink Angle:	118.5 Degrees Minimum And 121.5 Degrees Maximum
Material:	Titanium Alloy Uns R58450 Overall
Material Document And Classification:	Ams 4982 Assn Std Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2,cl 1 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218T5-5R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.