

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS14218T55R |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5320-01-367-6393 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



NO IMAGE
AVAILABLE

P/N MS14218T5-5R Specifications

| | |
|---|--|
| Fastener Length: | 0.3330 Inches Minimum And 0.3530 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.1550 Inches Minimum And 0.1580 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.2080 Inches Minimum And 0.2100 Inches Maximum |
| Minimum Tensile Strength: | 65000 Pounds Per Square Inch |
| Minimum Yield Strength: | 60000 Pounds Per Square Inch |
| Countersink Angle: | 118.5 Degrees Minimum And 121.5 Degrees Maximum |
| Material: | Titanium Alloy Uns R58450 Overall |
| Material Document And Classification: | Ams 4982 Assn Std Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,ty 2,cl 1 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218T5-5R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.