

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14218T56
Minimum Qty (MOQ):	20
NSN:	5320-01-206-5083
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N MS14218T5-6 Specifications

Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.042 Inches Nominal
Shank Diameter:	0.155 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.210 Inches Maximum
Minimum Tensile Strength:	65000 Pounds Per Square Inch
Minimum Yield Strength:	60000 Pounds Per Square Inch
Shear Strength:	50000 Single Pounds Per Square Inch
Countersink Angle:	118.5 Degrees Minimum And 121.5 Degrees Maximum
Heat Treatment:	Annealed Overall
Material:	Titanium Alloy Uns R58450 Overall
Material Document And Classification:	Ams 4982 Assn Std Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218T5-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.