

## Description

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS14218T59
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-268-5823
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



\* See page 2 for technical characteristics

## P/N MS14218T5-9 Specifications

<b>Fastener Length:</b>	0.552 Inches Minimum And 0.572 Inches Maximum
<b>Head Style:</b>	Countersunk W/ Reverse Chamfer
<b>Head Height:</b>	0.042 Inches Nominal
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.158 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.210 Inches Maximum
<b>Minimum Tensile Strength:</b>	65000 Pounds Per Square Inch
<b>Minimum Yield Strength:</b>	60000 Pounds Per Square Inch
<b>Shear Strength:</b>	50000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	118.5 Degrees Minimum And 121.5 Degrees Maximum
<b>Heat Treatment:</b>	Annealed Overall
<b>Material:</b>	Titanium Alloy Uns R58450 Overall
<b>Material Document And Classification:</b>	Ams 4982 Assn Std Single Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218T5-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.