

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | MS14218T612 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-01-206-5082 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS14218T6-12 Specifications

| | |
|--|--|
| Fastener Length: | 0.740 Inches Minimum And 0.760 Inches Maximum |
| Head Style: | Countersunk W/ Reverse Chamfer |
| Head Height: | 0.051 Inches Nominal |
| Shank Diameter: | 0.186 Inches Minimum And 0.189 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.258 Inches Maximum |
| Minimum Tensile Strength: | 65000 Pounds Per Square Inch |
| Minimum Yield Strength: | 60000 Pounds Per Square Inch |
| Shear Strength: | 50000 Single Pounds Per Square Inch |
| Countersink Angle: | 118.5 Degrees Minimum And 121.5 Degrees Maximum |
| Heat Treatment: | Annealed Overall |
| Material: | Titanium Alloy Uns R58450 Overall |
| Material Document And Classification: | Ams 4982 Assn Std Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218T6-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.