

**Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | MS14218T67                           |
| Minimum Qty (MOQ):      | 10 EA                                |
| NSN:                    | 5320-01-169-9637                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | EAR99                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE  
AVAILABLE

## P/N MS14218T6-7 Specifications

|  |  |
|--|--|
| <b>Fastener Length:</b>                      | 0.428 Inches Minimum And 0.448 Inches Maximum      |
| <b>Head Style:</b>                           | Countersunk W/ Reverse Chamfer                     |
| <b>Head Height:</b>                          | 0.051 Inches Nominal                               |
| <b>Shank Diameter:</b>                       | 0.186 Inches Minimum And 0.189 Inches Maximum      |
| <b>Shank Style:</b>                          | Straight W/radius Chamfered Tip                    |
| <b>Head Major Diameter:</b>                  | 0.258 Inches Maximum                               |
| <b>Countersink Angle:</b>                    | 118.5 Degrees Minimum And 121.5 Degrees Maximum    |
| <b>Material:</b>                             | Titanium Alloy Uns R58450 Overall                  |
| <b>Material Document And Classification:</b> | Ams 4982 Assn Std Single Material Response Overall |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14218T6-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.